COBB TESTER



COBB TESTER

This Equipment is used determines water absorption / penetration (cobb value) which is the quantity of water absorbed by surface of 100 cm² of the specimen on one side only in a specified time under a specified head of water.

Suitable For Testing as Per the following National & International Standards		
IS	1060 (Part I)- 1996	
ASTM	D 3285 - 93	
TAPPI	T 441 om-98	
FEFCO	TM 7 1997	



TECHNICAL SPECIFICATION			
DIMENSION IN MM (LxWxH)	152mm X 381mm X 254mm		
WEIGHT IN KG (TYPE ALUMINIUM)	10		
WEIGHT IN KG (TYPE SS)	12		
ROLLER WEIGHT IN KG	10		
CYLINDER	SS		

FEATURES:

- Easy to operate
- Provides Accurate Results

SPECIMEN	WATER HEAD	TIME OF
	MARK	TEST
PAPER	10 mm	1 Minute
CFB	25 mm	30 Minutes
BITUMEN WATERPROOF	100 mm	18 Hours
PAPER		

OTHER PRODUCTS ARE: -

•BURSTING STRENGTH TESTER •BOX COMPRESSION TESTER •SUBSTANCE INDICATOR (GSM) TESTER •MOISTURE TESTER •CRUSH TESTER •COBB TESTER •UNIVERSAL TESTER •TENSILE TESTER •VIBRATION TESTER •DROP TESTER •etc.



MCSPARR TEST SYSTEMS & INDUSTRIES

AN ISO 9001: 2015 CERTIFIED COMPANY

215, MAJHIPARA ROAD, THAKURPUKUR, KOLKATA – 700 063

PH: 9903878040/9007054956/8902005985 Email: info@mcsparr.org